



BLINDS + GLASS

A MODERN ALTERNATIVE TO TRADITIONAL BLINDS







ODL BLINDS + GLASS

is a blinds-between-glass IG panel
for doors and windows

Building upon our 80 year history of developing IG panels for doors, ODL continues to innovate in the blinds-between-glass category, where we have been the industry leader for over 20 years. Our industry relationships led us to discover that manufacturers, builders and homeowners wanted a simple solution that addressed and solved concerns about the safety, cleaning, and lack of ease associated with traditional blinds. That's why ODL created a modern alternative to traditional blinds.

Our innovation, **ODL Blinds + Glass**, allows for custom sizes and colors in as few as eight days, with the quality, reliability, and warranty you've come to expect from ODL. Homeowners and window manufacturers can rely on ODL Blinds + Glass for designs and options to fit every home.

Safety is a top priority for most consumers, and ODL Blinds + Glass proudly boasts certifications from two industry-leading child safety organizations. Best for Kids™ and Parents for Window Blind Safety™ advocate for cordless window coverings and educate consumers on products which greatly reduce or completely eliminate the risk of injury to children and pets.

Our goal is to provide quality products that improve your everyday life. In addition to a 10-year full replacement warranty, ODL offers the color options and configurations needed to compliment any architectural style. With ODL Blinds + Glass the possibilities are endless!





SINGLE AND DOUBLE
HUNG WINDOWS



7/8" BLINDS + GLASS RLT TOP FOR WINDOWS

PRODUCT FEATURES:

- Raise, lower, and tilt blinds
- Symmetric privacy channels
- EasyGlide Operator located top center (single operator)
- Low-E options:
 - Single: 270, 272, 340, 366
 - Dual: 189/270, 189/272, 189/340, 189/366
- Glass tint options:
 - Solar Gray and Solar Bronze
- NEAT Options:
 - 270, 366, 189/270, and 189/366
- 10-year full warranty

OPERATOR:



EasyGlide Operator
0.512" thickness
(Six Color Options)


PROGRAM DETAILS:

- Dimensions:
 - 15" – 54" wide
 - 12" – 41" tall
 - IG Thickness : 7/8" or 1" (with 6mm external glass option)
 - Tempered or Annealed Glass - up to 9 ft²
 - Custom size increments 1/16" (height & width)
 - Minimum Quantity: 1
- * No more than 36" in one direction

AVAILABLE COLORS:



BLINDS SIZE RANGE[†]



7/8" RLT -TOP ANNEALED & TEMPERED

Single Operator
Max IG Size: 9 ft²

- 2 Ladder Cords
- 3 Ladder Cords
- 4 Ladder Cords
- 5 Ladder Cords



SINGLE AND DOUBLE
HUNG WINDOWS



7/8" BLINDS + GLASS TILT TOP FOR WINDOWS

PRODUCT FEATURES:

- Blinds with tilt operation
- Symmetric privacy channels
- Tilt operator located in the top right corner
- Low-E options:
Single: 270, 272, 340, 366
Dual: I89/270, I89/272, I89/340, I89/366
- Glass tint options:
Solar Gray and Solar Bronze
- NEAT Options:
270, 366, I89/270, and I89/366
- 10-year full warranty

OPERATOR:



Tilt Operator
0.629" thickness
(Six Color Options)


PROGRAM DETAILS:

- Dimensions:
8" – 54" wide
12" – 68" tall
IG Thickness : 7/8" or 1" (with 6mm external glass option)
- Tempered or Annealed glass - up to 9 ft²
- Custom size increments 1/16" (height & width)
- Minimum Quantity: 1
- * No more than 36" in one direction

AVAILABLE COLORS:



BLINDS SIZE RANGE[†]



7/8" TILT ANNEALED & TEMPERED

Single Operator
Max IG Size: 9 ft²

- 2 Ladder Cords
- 3 Ladder Cords
- 4 Ladder Cords



CASEMENT/FIXED



SLIDING



SWING



AWNING



SLIDING PATIO DOORS



7/8" BLINDS + GLASS FOR WINDOWS AND SLIDING PATIO DOORS

PRODUCT FEATURES:

- Ideal for use in both windows and sliding patio doors. (awning, casement, fixed, sliding and bay windows; and sliding patio doors)
- EasyGlide left or right hand operator location options
High or low operator position
between 32" - 48" high
- Symmetric or Asymmetric privacy channel options
- Low-E options:
Single: 270, 272, 340, 366
Dual: 189/270, 189/272, 189/340, 189/366
- Glass tint options:
Solar Gray and Solar Bronze
- NEAT Options:
270, 366, 189/270, and 189/366
- 10-year full warranty

OPERATORS:



EasyGlide Operator
0.539" thickness
(Six Color Options)

PROGRAM DETAILS:

- Dimensions:
8" – 48" wide⁺
18" – 80" tall
IG Thickness: 7/8" or 1"
(with 6mm external glass option)
- Tempered glass - up to 18 ft²*
- Annealed glass - up to 15 ft²*
- Custom size increments 1/16" (height & width)
- Minimum Quantity: 1


⁺Widths below 10" will have an asymmetrical design

^{*}No more than 36" in one direction

AVAILABLE COLORS:



BLINDS SIZE RANGE⁺



7/8" ANNEALED & TEMPERED

- Dual Operator (Tempered Only)
Max IG Size: 18 ft²
48" or greater in height
Operator Location
(Left or Right)
- Dual Operator
Max IG Size: 15 ft²
48" or greater in height
Operator Location
(Left or Right)
- Single Operator
Max IG Size: 12 ft²
48" or Less in height
Operator Location
(Left or Right)



CASEMENT/FIXED



SLIDING



SWING



AWNING



SLIDING PATIO DOORS



1" BLINDS + GLASS FOR WINDOWS AND SLIDING PATIO DOORS

PRODUCT FEATURES:

- Ideal for use in both windows and sliding patio doors. (awning, casement, fixed, sliding and bay windows; and sliding patio doors)
- Symmetric or A-symmetric privacy channel options
- EasyGlide left or right hand operator location options
 - High or low operator position for single operator above 32" high
- Low-E options:
 - Single: 270, 272, 340, 366
 - Dual: 189/270, 189/272, 189/340, 189/366
- Glass tint options:
 - Solar Gray and Solar Bronze
- NEAT Options:
 - 270, 366, 189/270, and 189/366
- 10-year full warranty

OPERATORS:



EasyGlide Operator
0.539" thickness
(Six Colors)



SlimLine Operator
0.323" thickness
(White Only)

PROGRAM DETAILS:

- Dimensions:
 - 8" – 80" wide[†]
 - 14" – 80" tall
 - IG Thickness: 1" or 1 1/8" (with 6mm external glass option)
- Tempered glass - up to 17 ft²*
- Annealed glass - up to 15 ft²*
- Custom size increments 1/16" (height & width)
- Minimum Quantity: 1

[†]Widths below 10" will have an asymmetrical design

* No more than 36" in one direction

AVAILABLE COLORS:



ESPRESSO



SAND



SILVER MOON



SLATE GRAY




TAN



WHITE

BLINDS SIZE RANGE[†]



WIDTH

†1/16" INCREMENT



CASEMENT/FIXED



SLIDING



SWING



AWNING



SLIDING PATIO DOORS



1" BLINDS + GLASS XL FOR WINDOWS AND SLIDING PATIO DOORS

PRODUCT FEATURES:

- Ideal for large format windows and sliding patio doors (awning, casement, fixed, sliding and bay windows, and sliding patio doors)
- EasyGlide left- or right-hand operator location
- Low-E options:
Single: 270, 272, 340, 366
Dual: 189/270, 189/272, 189/340, 189/366
- 10-year full warranty

OPERATORS:



EasyGlide Operator
0.539"
thickness
(Six Colors)


PROGRAM DETAILS:

- Dimensions:
9" – 63" wide
46" – 90" tall
1" thick
- Tempered glass only - up to 28 ft²
- Custom size increments 1/16" (height & width)
- Minimum Quantity: 1
- * No more than 48" in one direction

AVAILABLE COLORS:



BLINDS SIZE RANGE[‡]





SLIDING PATIO DOORS



1" BLINDS + GLASS CLASSIC FOR WINDOWS AND SLIDING PATIO DOORS

PRODUCT FEATURES:

- Raise, lower, and tilt blinds for use in sliding patio doors
- Classic or Low-Profile dual left - or right-hand operator location
- Low-E options:
 - Single: 270, 272, 366
 - Dual: 189/270, 189/272, 189/366
- 10-year full warranty

OPERATORS:

CLASSIC



0.667" THICKNESS

LOW-PROFILE



0.438" THICKNESS

PROGRAM DETAILS:


- Dimensions:
 - 14" – 36" wide
 - 42" – 80" tall
 - 1" thick
- Tempered glass only - up to 17 ft²
- Custom size increments 1/16" (height & width)
- Minimum Quantity: 1
- * No more than 36" in one direction

AVAILABLE COLORS:




WHITE

1" CLASSIC SIZE RANGE



TECHNICAL DRAWINGS & SPECIFICATIONS




OPERATION

Blind Function	Raise, Lower, and Tilt
EasyGlide Operator	Clear Overmold/Two Shot
Single Operator	Annealed glass: Up to 9 ft ² or Tempered glass: Up to 9 ft ²
Capillary Tube	Do not block, crush or cut
Operator Position	Top Center

CODE OF COMPLIANCE


IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036 (Annealed) & C1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations



MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	Annealed or tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (i89)
Glass Tint	Solar Gray or Solar Bronze glass panel
Blind Slat	10mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer

TECHNICAL DRAWINGS & SPECIFICATIONS




OPERATION

Blind Function	Tilt
EasyGlide Operator	Clear Overmold/Two Shot
Single Operator	Annealed glass: Up to 9 ft ² or Tempered glass: Up to 9 ft ²
Capillary Tube	Do not block, crush or cut
Operator Position	Top Right

CODE OF COMPLIANCE



IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036 (Annealed) & C1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations



MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	Annealed or tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface Low-E (i89)
Glass Tint	Solar Gray or Solar Bronze glass panel
Blind Slat	11.5 mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer

TECHNICAL DRAWINGS & SPECIFICATIONS



OPERATION

Blind Function	Raise, Lower, and Tilt
EasyGlide Operator	Clear Overmold/Two Shot
Single Operator	48" or less in height
Dual Operator	48" or greater in height
Capillary Tube	Do not block, crush or cut
Operator Hand	Left or right
Operator Position	High or low (single operator only above 32" in height)


CODE OF COMPLIANCE

IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036 (Annealed) & C1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations

MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	Annealed (limited to 15ft²) or tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (i89)
Glass Tint	Solar Gray or Solar Bronze glass panel
Blind Slat	10 mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer


TECHNICAL DRAWINGS & SPECIFICATIONS




OPERATION

Blind Function	Raise, Lower, and Tilt
EasyGlide Operator	Clear Overmold/Two Shot
SlimLine Operator	Single Shot
Dual Operator (minimum 48" high)	Up to 17 ft ²
Dual or Single Operator	See size chart for details
Single Operator	Annealed glass: Up to 12 ft ² Tempered glass: Up to 12 ft ²
Capillary Tube	Do not block, crush or cut
Operator Hand	Left or right
Operator Position	High or low (single operator only above 32" in height)

EASYGLIDE OPERATOR*




SLIMLINE OPERATOR



MATERIALS


Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	Annealed (limited to 15ft ²) or tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (i89)
Glass Tint	Solar Gray or Solar Bronze glass panel
Blind Slat	12.5 mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer



CODE OF COMPLIANCE

IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM C1036 (Annealed) & C1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations

TECHNICAL DRAWINGS & SPECIFICATIONS




OPERATION

Blind Function	Raise, Lower, and Tilt
EasyGlide Operator	Clear Overmold/Two Shot
Dual Operator	Up to 28 ft ²
Capillary Tube	Do not block, crush or cut
Operator Hand	Left or right

CODE OF COMPLIANCE


IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	C1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	CAD available for simulations



MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	4mm tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (i89)
Blind Slat	10mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer

TECHNICAL DRAWINGS & SPECIFICATIONS




OPERATION

Blind Function	Raise, Lower, and Tilt
Dual Operator	Tempered up to 17 ft ²
Operator Sizes	Classic Design: 0.667" Thickness Low Profile Design: 0.438 Thickness
Capillary Tube	Do not block, crush or cut
Operator Hand	Right/Left

CODE OF COMPLIANCE

IGCC (seal)	ASTM E2190 seal certification
ANSI (glass)	ANSI Z97.1 safety glazing (Applies to tempered glass only)
ASTM (glass)	ASTM 1048 (Tempered)
ANSI (safety)	ANSI / WCMA A100.1
ENERGY STAR®	Will help your window achieve ENERGY STAR® performance when select Low-E glass is employed
NFRC	Reference Certified Product Directory for sliding door examples (CAD available for simulations)



MATERIALS

Spacer	Intercept®, tin plated steel
Glass (Clear or Low-E)	Tempered safety glass
Single Low-E	2nd surface soft coat (270, 272, 340, 366)
Dual Low-E	4th surface hard coat Low-E (189)
Blind Slat	12.5mm wide aluminum UV stabilized coating
Sealant	Dual seal equivalent
Desiccant	Desiccant matrix (moisture & chemical management)
Decorative Cover Caps	UV stabilized, heat tolerant polymer





FEATURES that go beyond

WHY **BLINDS + GLASS?**

- Allows consumers to further **CUSTOMIZE** their windows and doors with well-designed light and privacy solutions
- **INCREASES MARGINS** with higher pricing options
- Establishes you as a **MARKET LEADER** while expanding your product portfolio
- Built for long-term performance with **10-YEAR WARRANTY**
- Coordinates with **PATIO AND ENTRY DOOR** products to create a more cohesive look in the home
- A **POPULAR** choice for open dining, kitchen, baths, large format windows, and family areas of the home
- Offers consumers **LESS MAINTENANCE** and **SAFER OPTIONS** for homes with children and pets
- **SIX COLOR OPTIONS** that coordinate with interiors and exteriors of the home



IG PANEL PROGRAM DETAILS

	7/8" RLT-TOP	7/8" TILT	7/8"	1"	1" XL	1" CLASSIC
IG WIDTH RANGES IG HEIGHT RANGES IG THICKNESS	15"-54" wide 12"-41" tall 7/8" thick or 1" (with 6mm external glass option)	8"-54" wide 12"-68" tall 7/8" thick or 1" (with 6mm external glass option)	8"-48" wide 18"-80" tall 7/8" thick or 1" (with 6mm external glass option)	8"-80" wide 14"-80" tall 1" thick or 1 1/8" (with 6mm external glass option)	9"-63" wide 46"-90" tall 1" thick	14"-36" wide 42"-80" tall 1" thick
MAXIMUM SQ FT	9	9	18	17	28	17
GLASS TYPE	Tempered or Annealed glass up to 9 ft ²	Tempered or Annealed glass up to 9 ft ²	Tempered glass up to 18 ft ² Annealed glass up to 15 ft ²	Tempered glass up to 17 ft ² Annealed glass up to 15 ft ²	Tempered glass only up to 28 ft ²	Tempered glass only up to 17 ft ²
LOW-E OPTIONS	Single: 270, 272, 340, 366 Dual: i89/270, i89/272, i89/340, i89/366	Single: 270, 272, 340, 366 Dual: i89/270, i89/272, i89/340, i89/366	Single: 270, 272, 340, 366 Dual: i89/270, i89/272, i89/340, i89/366	Single: 270, 272, 340, 366 Dual: i89/270, i89/272, i89/340, i89/366	Single: 270, 272, 340, 366 Dual: i89/270, i89/340, i89/366, i89/272	Single: 270, 272, 340, 366 Dual: i89/270, i89/272, i89/366
GLASS TINT	Solar Gray or Solar Bronze	Solar Gray or Solar Bronze	Solar Gray or Solar Bronze	Solar Gray or Solar Bronze	N/A	N/A
OPERATOR QUANTITY	Single Operator Only	Single Operator Only	Single Operator 48" Or Less Dual Operator 48" Or Greater	Single Operator up to 12ft ² , Dual op 48" high or greater	Dual Operator Only	Dual Operator Only
OPERATOR OPTIONS	Top center operator position IG only EasyGlide design 0.512" thickness	Upper right corner operator position IG only Tilt design 0.629" thickness	High or low operator position Left or right- hand operator EasyGlide design 0.539" thickness	High or low operator position Left or right- hand operator EasyGlide design 0.539" thickness SlimLine design* 0.323" thickness	Left or right- hand operator EasyGlide design 0.539" thickness	Classic design 0.667" thickness Left or right- hand operator Low profile design 0.438" thickness
BLIND COLOR	Espresso, Sand, Silver Moon, Slate Gray, Tan, White	Espresso, Sand, Silver Moon, Slate Gray, Tan, White	Espresso, Sand, Silver Moon, Slate Gray, Tan, White	Espresso, Sand, Silver Moon, Slate Gray, Tan, White	Espresso, Sand, Silver Moon, Slate Gray, Tan, White	White
MINIMUM QUANTITY	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1	Low-E: 1 CL/CL: 1
WORKING DAYS TO DELIVER	Annealed: 8 business days + transit Tempered: 12 business days + transit	Annealed: 8 business days + transit Tempered: 12 business days + transit	Annealed: 8 business days + transit Tempered: 12 business days + transit	Annealed: 8 business days + transit Tempered: 12 business days + transit	Tempered: 19 business days + transit	Tempered: 12 business days + transit
10 YEAR FULL WARRANTY	✓	✓	✓	✓	✓	✓

- * SlimLine Operator available in white
- + Widths below 10" will have an asymmetrical design
- See size chart for limitations



WARNING!
Cancer and Reproductive Harm -
www.P65Warnings.ca.gov